

SPOK[®] MAXPAGE



PAGING TERMINAL

Spok MAXPage is a stand-alone desktop paging terminal with the capacity to store up to 1,000 pagers. Its large backlit keypad and LCD allows you to send free-form numeric messages directly from the terminal as well as stored alphanumeric messages using the four on-board function keys.

BUILT-IN TRANSMITTER

Available in VHF or UHF, the built-in transmitter can be programmed using the keypad frequency. Select two or four Watts of power to give you up to a one-mile range.

ALPHANUMERIC PAGING (OPTIONAL)

For those companies that require alphanumeric paging, Spok MAXPage has a keyboard port. To send alphanumeric messages or configure the Spok MAXPage terminal, simply plug in the optional Spok MAXPage keyboard.

TELEPHONE PORT (OPTIONAL)

Spok MAXPage can be connected to a telephone port so that anyone can dial into the terminal to send messages remotely. Callers are greeted by a series of voice prompts that guide the caller through the simple message dispatch process.

RS232/SERIAL INTERFACE (OPTIONAL)

Spok MAXPage also includes a serial port which can be used to receive and relay messages from any device that sends messages in TAP, Visiplex, COMP, Scope or TEKK protocols. Spok MAXPage seamlessly transmits these messages as they arrive.

ALARM INPUTS

Spok MAXPage contains four dry contact alarm inputs. Once an alarm is activated, a predefined 20-character alphanumeric message is sent to a pager or group of pagers. If the alarm is not reset within a predetermined time, the alarm message can be escalated to another pager or group.

WINDOWS[®] USER INTERFACE (OPTIONAL)

As an option to the on-board keypad or PS/2 keyboard interface, Spok MAXPage can be operated using the optional Windows software. Included in the software are special functions for the operation and configuration of Spok's coaster pagers.

MAXPAGE: KEY BENEFITS

- 1,000 pager capacity
- Up to one-mile range
- Numeric and alphanumeric
- Voice-prompted telephone interface
- Serial interface (RS232)
- Four alarm inputs
- Windows interface



DATASHEET

TECHNICAL SPECIFICATIONS

SPOK MAXPAGE	
Recipient Capacity	1000 pages max
Group Capacity	20 groups each with up to 10 members
Licensable Options	Alarm inputs, PBX, PS2 keyboard, serial port
Maximum Message Length	200 characters (keypad/keyboard)
Time	24-hour format
Alarm Inputs	One-four inputs (via RJ45 socket)
Alarm Contact Style	Dry contact type (common ground)
Alarm Escalation	Second recipient available after 0-9999 second delay
Alarm Configuration	Recipient, delay, beep code and message configurable for each input
Internal Transmitter	2 or 4 Watts
Operating Frequency	VHF:148-174 Mhz UHF: 440-470 Mhz
Supported Transmission Protocol	POCSAG 512, 1200, 2400 bps
Encoding	Alphanumeric, numeric, tone-only
Support Serial Protocols	TAP, COMP1, COMP2, Scope, TEKK, Visiplex
Power Requirements	12-13.8V DC regulated
Current	2 Amps max
Dimensions	226(l) x 160(w) x 70 (h) mm 8.9(l) x 6.3(w) x 2.75(h) inches
Weight	1.0kg (2.2lb)
Reminder Messages	10 reminders total – comprised of time, recipient, and message
Approvals	FCC Part 15, FCC Part 68, CE, Industry Canada, C tick

